

API Tubing Table



www.tarponpipe.com

Tubing Table

O.D. (inch)	NOMINAL WEIGHT T&C (lbs/ft)				GRADE	COLLAPSE (psi)	INTERNAL YIELD PRESSURE at MINIMUM YIELD (psi)				JOINT STRENGTH (lbs)			BODY YIELD (lbs)	WALL (inch)	I.D. (inch)	DRIFT DIAMETER (inch)		
	NUE	T&C	EUE	T&C			PE, NUE T&C	BUTTR. T&C	EUE T&C		NUE T&C	BUTTR. T&C	EUE T&C						
									REGULAR CPL.	SPEC. CPL.									
1	1.14		1.2		H-40	7680		7530		7530			6360		13300	13300	0.113	0.824	0.73
1	1.14		1.2		J-55	10560		10360		10360			8740		18300	18300	0.113	0.824	0.73
1	1.14		1.2		LS-65	12480		12240		12240			10330		21600	21600	0.113	0.824	0.73
1	1.14		1.2		L-80	15370		15070		15070			12720		26600	26600	0.113	0.824	0.73
1	1.14		1.2		N-80	15370		15070		15070			12720		26600	26600	0.113	0.824	0.73
1	1.14		1.2		T-95	18250		17890		17890			15100		31600	31600	0.113	0.824	0.73
1 1/4	1.7		1.8		H-40	7270		7080		7080			10960		19800	19800	0.133	1.049	0.955
1 1/4	1.7		1.8		J-55	10000		9730		9730			15060		27200	27200	0.133	1.049	0.955
1 1/4	1.7		1.8		LS-65	11820		11500		11500			17800		32100	32100	0.133	1.049	0.955
1 1/4	1.7		1.8		L-80	14550		14160		14160			21910		39500	39500	0.133	1.049	0.955
1 1/4	1.7		1.8		N-80	14550		14160		14160			21910		39500	39500	0.133	1.049	0.955
1 1/4	1.7		1.8		T-95	17270		16810		16810			26020		46900	46900	0.133	1.049	0.955
1 1/2	2.3		2.4		H-40	6180		5900		5900			15530		26700	26700	0.14	1.38	1.286
1 1/2	2.3		2.4		J-55	8490		8120		8120			21360		36800	36800	0.14	1.38	1.286
1 1/2	2.3		2.4		LS-65	10040		9590		9590			25240		43500	43500	0.14	1.38	1.286
1 1/2	2.3		2.4		L-80	12360		11810		11810			31060		53500	53500	0.14	1.38	1.286
1 1/2	2.3		2.4		N-80	12360		11810		11810			31060		53500	53500	0.14	1.38	1.286

API Tubing Table



www.tarponpipe.com

Tubing Table

O.D. (inch)	NOMINAL WEIGHT T&C (lbs/ft)		GRADE	COLLAPSE (psi)	INTERNAL YIELD PRESSURE at MINIMUM YIELD (psi)				JOINT STRENGTH (lbs)			BODY YIELD (lbs)	WALL (inch)	I.D. (inch)	DRIFT DIAMETER (inch)
	NUE T&C	EUE T&C			PE, NUE T&C	BUTTR. T&C	EUE T&C		NUE T&C	BUTTR. T&C	EUE T&C				
							REGULAR CPL.	SPEC. CPL.							
1 1/2	2.3	2.4	T-95	14670	14020		14020		36900		63500	63500	0.14	1.38	1.286
2	2.75	2.9	H-40	5640	5340		5340		19100		32000	32000	0.145	1.61	1.516
2	2.75	2.9	J-55	7750	7350		7350		26300		44000	44000	0.145	1.61	1.516
2	2.75	2.9	LS-65	9160	8680		8680		31000		52000	52000	0.145	1.61	1.516
2	2.75	2.9	L-80	11280	10680		10680		38200		64000	64000	0.145	1.61	1.516
2	2.75	2.9	N-80	11280	10680		10680		38200		64000	64000	0.145	1.61	1.516
2	2.75	2.9	T-95	13440	12690		12690		45300		75900	75900	0.145	1.61	1.516
2 1/16	3.25		H-40	5590	5290		5290				35700	37400	0.156	1.751	1.657
2 1/16	3.25		J-55	7690	7280		7280				49100	51400	0.156	1.751	1.657
2 1/16	3.25		LS-65	9090	8600		8600				57900	60700	0.156	1.751	1.657
2 1/16	3.25		L-80	11180	10590		10590				71400	74800	0.156	1.751	1.657
2 1/16	3.25		N-80	11180	10590		10590				71400	74800	0.156	1.751	1.657
2 1/16	3.25		T-95	13240	12570		12570				84700	88800	0.156	1.751	1.657
2 1/16	3.25		P-110	15680	14560		14560				98100	102800	0.156	1.751	1.657
2 3/8	4		H-40	5230	4920				30100			46300	0.167	2.041	1.947
2 3/8	4		J-55	7190	6770				41400			63700	0.167	2.041	1.947
2 3/8	4		L-80	9980	9840				60300			92700	0.167	2.041	1.947

API Tubing Table



www.tarponpipe.com

Tubing Table

O.D. (inch)	NOMINAL WEIGHT T&C (lbs/ft)				GRADE	COLLAPSE (psi)	INTERNAL YIELD PRESSURE at MINIMUM YIELD (psi)				JOINT STRENGTH (lbs)			BODY YIELD (lbs)	WALL (inch)	I.D. (inch)	DRIFT DIAMETER (inch)		
	NUE	T&C	EUE	T&C			PE, NUE T&C	BUTTR. T&C	EUE T&C		NUE T&C	BUTTR. T&C	EUE T&C						
									REGULAR CPL.	SPEC. CPL.									
2 3/8	4				N-80	9980	9840						60300			92700	0.167	2.041	1.947
2 3/8	4				T-95	11410	11690						71600			110000	0.167	2.041	1.947
2 3/8	4.6		4.7		H-40	5890	5600	5600	5600	5600	5600	5600	36000	52200	52200	52200	0.19	1.995	1.901
2 3/8	4.6		4.7		J-55	8100	7700	7700	7700	7700	7700	7700	49500	71700	71700	71700	0.19	1.995	1.901
2 3/8	4.6		4.7		LS-65	9570	9100	9100	9100	9100	9100	9100	58400	84800	84800	84800	0.19	1.995	1.901
2 3/8	4.6		4.7		L-80	11780	11200	11200	11200	11200	11200	11200	71900	104300	104300	104300	0.19	1.995	1.901
2 3/8	4.6		4.7		N-80	11780	11200	11200	11200	11200	11200	11200	71900	104300	104300	104300	0.19	1.995	1.901
2 3/8	4.6		4.7		T-95	13980	13300	13300	13300	13300	13300	13300	85400	123900	123900	123900	0.19	1.995	1.901
2 3/8	4.6		4.7		P-110	16130	15400	15400	15400	15400	15400	15400	98900	143500	143500	143500	0.19	1.995	1.901
2 3/8	5.8		5.95		L-80	15280	14970	14850	14850	14850	11430	11430	103000	135400	135400	135400	0.254	1.867	1.773
2 3/8	5.8		5.95		N-80	15280	14970	14850	14850	11430	11430	11430	103000	135400	135400	135400	0.254	1.867	1.773
2 3/8	5.8		5.95		T-95	18150	17780	17640	17640	17640	13570	13570	122300	160800	160800	160800	0.254	1.867	1.773
2 3/8	5.8		5.95		P-110	21010	20590	20590	20590	20430	15720	15720	141600	186200	186200	186200	0.254	1.867	1.773

2 7/8	6.4		6.5		H-40	5580	5280	5280	5280	5280	5280	5280	52800	72500	72500	72500	0.217	2.441	2.347
2 7/8	6.4		6.5		J-55	7680	7260	7260	7260	7260	7260	7260	72600	99700	99700	99700	0.217	2.441	2.347
2 7/8	6.4		6.5		LS-65	9070	8590	8590	8590	8590	8590	8590	85800	117800	117800	117800	0.217	2.441	2.347
2 7/8	6.4		6.5		L-80	11170	10570	10570	10570	10570	10570	10570	105600	145000	145000	145000	0.217	2.441	2.347
2 7/8	6.4		6.5		N-80	11170	10570	10570	10570	10570	10570	10570	105600	145000	145000	145000	0.217	2.441	2.347
2 7/8	6.4		6.5		T-95	12940	12550	12550	12550	12550	12550	12550	125400	172100	172100	172100	0.217	2.441	2.347

API Tubing Table



www.tarponpipe.com

Tubing Table

O.D. (inch)	NOMINAL WEIGHT T&C (lbs/ft)		GRADE	COLLAPSE (psi)	INTERNAL YIELD PRESSURE at MINIMUM YIELD (psi)				JOINT STRENGTH (lbs)			BODY YIELD (lbs)	WALL (inch)	I.D. (inch)	DRIFT DIAMETER (inch)		
	NUE	T&C			EUE	T&C	PE, NUE T&C	BUTTR. T&C	EUE T&C		NUE T&C					BUTTR. T&C	EUE T&C
									REGULAR CPL.	SPEC. CPL.							
2 7/8	6.4		6.5	P-110	14550	14530	14530	14530	14530	145200	199300	199300	199300	0.217	2.441	2.347	
2 7/8	7.8		7.9	L-80	13890	13440	13440	13440	11040	140900	180300	180300	180300	0.276	2.323	2.229	
2 7/8	7.8		7.9	N-80	13890	13440	13440	13440	11040	140900	180300	180300	180300	0.276	2.323	2.229	
2 7/8	7.8		7.9	T-95	16490	15960	15960	15960	13110	167300	214100	214100	214100	0.276	2.323	2.229	
2 7/8	7.8		7.9	P-110	19090	18480	18480	18480	15180	193700	247900	247900	247900	0.276	2.323	2.229	
2 7/8	8.6		8.7	L-80	15300	15000	15000	14950	11040	159300	198700	198700	198700	0.308	2.259	2.165	
2 7/8	8.6		8.7	N-80	15300	15000	15000	14950	11040	159300	198700	198700	198700	0.308	2.259	2.165	
2 7/8	8.6		8.7	T-95	18170	17810	17810	17750	13110	189200	236000	236000	236000	0.308	2.259	2.165	
2 7/8	8.6		8.7	P-110	21040	20620	20620	20560	15180	219100	273200	273200	273200	0.308	2.259	2.165	
3 1/2	7.7			H-40	4630	4320				65100		89100		0.216	3.068	2.943	
3 1/2	7.7			J-55	5970	5940				89500		122600		0.216	3.068	2.943	
3 1/2	7.7			L-80	7870	8640				130100		178300		0.216	3.068	2.943	
3 1/2	7.7			N-80	7870	8640				130100		178300		0.216	3.068	2.943	
3 1/2	7.7			T-95	8850	10260				154500		211700		0.216	3.068	2.943	
3 1/2	9.2	9.3		H-40	5380	5080	5080	5080	5080	79500	103600	103600	103600	0.254	2.992	2.867	
3 1/2	9.2	9.3		J-55	7400	6990	6990	6990	6990	109400	142500	142500	142500	0.254	2.992	2.867	
3 1/2	9.2	9.3		LS-65	8750	8260	8260	8260	8260	129300	168400	168400	168400	0.254	2.992	2.867	
3 1/2	9.2	9.3		L-80	10540	10160	10160	10160	10160	159100	207200	207200	207200	0.254	2.992	2.867	
3 1/2	9.2	9.3		N-80	10540	10160	10160	10160	10160	159100	207200	207200	207200	0.254	2.992	2.867	

API Tubing Table



www.tarponpipe.com

Tubing Table

O.D. (inch)	NOMINAL WEIGHT T&C (lbs/ft)		GRADE	COLLAPSE (psi)	INTERNAL YIELD PRESSURE at MINIMUM YIELD (psi)				JOINT STRENGTH (lbs)			BODY YIELD (lbs)	WALL (inch)	I.D. (inch)	DRIFT DIAMETER (inch)
	NUE T&C	EUE T&C			PE, NUE T&C	BUTTR. T&C	EUE T&C		NUE T&C	BUTTR. T&C	EUE T&C				
							REGULAR CPL.	SPEC. CPL.							
3 1/2	9.2	9.3	T-95	12080	12070	12070	12070	12070	188900	246100	246100	246100	0.254	2.992	2.867
3 1/2	9.2	9.3	P-110	13530	13970	13970	13970	13970	218700	284900	284900	284900	0.254	2.992	2.867
3 1/2	10.2		H-40	6060	5780				92500			116600	0.289	2.922	2.797
3 1/2	10.2		J-55	8330	7950				127300			160300	0.289	2.922	2.797
3 1/2	10.2		LS-65	9850	9390				150400			189500	0.289	2.922	2.797
3 1/2	10.2		L-80	12120	11560				185100			233200	0.289	2.922	2.797
3 1/2	10.2		N-80	12120	11560				185100			233200	0.289	2.922	2.797
3 1/2	10.2		T-95	14390	13730				219800			277000	0.289	2.922	2.797
3 1/2	12.7	12.95	L-80	15310	15000	15000	15000	10660	246400		294500	294500	0.375	2.75	2.625
3 1/2	12.7	12.95	N-80	15310	15000	15000	15000	10660	246400		294500	294500	0.375	2.75	2.625
3 1/2	12.7	12.95	T-95	18180	17810	17810	17810	12660	292600		349700	349700	0.375	2.75	2.625
3 1/2	12.7	12.95	P-110	21050	20630	20630	20630	14650	338800		405000	405000	0.375	2.75	2.625
4	9.5		H-40	4050	3960				72000		107200		0.226	3.548	3.423
4	9.5		J-55	5110	5440				99000		147400		0.226	3.548	3.423
4	9.5		L-80	6590	7910				144000		214400		0.226	3.548	3.423
4	9.5		N-80	6590	7910				144000		214400		0.226	3.548	3.423
4	9.5		T-95	97310	9390				171000		254600		0.226	3.548	3.423
4		11	H-40	4900	4590		4590				123100	123100	0.262	3.476	3.351
4		11	J-55	6590	6300		6300				169200	169200	0.262	3.476	3.351

API Tubing Table

Tubing Table

O.D. (inch)	NOMINAL WEIGHT T&C (lbs/ft)		GRADE	COLLAPSE (psi)	INTERNAL YIELD PRESSURE at MINIMUM YIELD (psi)				JOINT STRENGTH (lbs)			BODY YIELD (lbs)	WALL (inch)	I.D. (inch)	DRIFT DIAMETER (inch)		
	NUE	T&C			EUE	T&C	PE, NUE T&C	BUTTR. T&C	EUE T&C		NUE T&C					BUTTR. T&C	EUE T&C
									REGULAR CPL.	SPEC. CPL.							
4		11	L-80	8800	9170		9170				246100	246100	0.262	3.476	3.351		
4		11	C-90	9590	10320		10320				276900	276900	0.262	3.476	3.351		
4		11	T-95	9980	10890		10890				292300	292300	0.262	3.476	3.351		
4 1/2	12.6	12.75	H-40	4490	4220		4220		104400		144000	144000	0.271	3.958	3.833		
4 1/2	12.6	12.75	J-55	5730	5800		5800		143500		198000	198000	0.271	3.958	3.833		
4 1/2	12.6	12.75	L-80	7500	8430		8430		208700		288000	288000	0.271	3.958	3.833		
4 1/2	12.6	12.75	N-80	7500	8430		8430		208700		288000	288000	0.271	3.958	3.833		
4 1/2	12.6	12.75	T-95	8410	10010		10010		247900		342000	342000	0.271	3.958	3.833		